

标准导程参数 30°

TSL 30°

磨光 Ground OD				
Ø	ID	CHD	Ø	lead
福雷孔产 品外径 mm	孔径 mm	孔间 距 mm	客户成品 外径 mm	mm
2.2	0.4	1.1	请就具体产品设计要 求咨询 tzheng@forecreu.com	
2.7	0.45	1.3		
3.2	0.5	1.5		
3.7	0.55	1.7		
4.2	0.65	1.9		
4.7	0.7	2.1		
5.2	0.75	2.3		
5.7	0.85	2.5		
6.3	0.95	3.2		
6.8	1	3.4		
7.3	1.1	3.7		
7.8	1.15	3.9		
8.3	1.2	4.1		
8.8	1.3	4.4	8.5	46,25
9.3	1.35	4.6	9.0	48,97
9.8	1.4	4.8	9.5	51,69
10.3	1.5	5	10.0	54,41
10.8	1.55	5.3	10.5	57,13
11.3	1.6	5.5	11.0	59,86
11.8	1.7	5.7	11.5	62,58
12.3	1.75	6	12.0	65,3
12.8	1.8	6.2	12.5	68,02
13.3	1.9	6.4	13.0	70,74

黑皮 Black OD				
Ø	ID	CHD	Ø	lead
福雷孔产 品外径 mm	孔径 mm	孔间 距 mm	客户成品 外径 mm	mm
14.0	1.9	6.4	13	70,74
15.0	2	6.9	14	76,18
16.0	2.2	7.3	15	81,62
17.0	2.3	7.8	16	87,06
18.0	2.5*	8.4*	17	92,5
19.0	2.6	8,8*	18	97,95
20.0	2.7	9.3	19	103,39
21.0	2.9	9.8	20	108,83
22.0	3	10.2	21	114,27
23.0	3.1	10.7	22	119,71
24.0	3.3	11.1	22	119,71
25.0	3.4	11.6	23	125,15
26.0	3.5	12.1	24	130,59
27.0	3.7	12.5	25	136,03
28.0	3.8	13	26	141,48
29.0	3.9	13.4	27	146,92
30.0	4.1	13.9	28	152,36
31.0	4.2	14.3	29	157,8
32.0	4.3	14.8	30	163,24
33.0	4.5	15.3	31	168,68
34.0	4.6	15.7	32	174,12
35.0	4.7	16.2	33	179,57
36.0	4.9	16.6	34	185,01
37.0	5	17.1	35	190,45
38.0	5.2	17.6	36	195,89
39.0	5.3	18	37	201,33
40.0	5.4	18.5	38	206,77

OD 18: 2.5 and 8.4 for M2,
2.4 and 8.3 for M35 and PM30.
OD 19: 8.8 for M2,
8.7 for M35 and PM30.

STANDARD LEAD 30°

非合同性质文件

FIC 310 版本: 04.2014

FORECREU Tooling

Ch Forecreu SAS. - 地址: Chemin de Saint Amand, F-03600 Malicorne, France- 电话: +33 (0)4 70 64 43 37- 传真: +33 (0)4 70 09 08 70
常州福雷孔新材料科技有限公司 -地址: 常州武进高新区西湖路8号5C103室 -邮编: 213164 -电话: 0519 86225260 -传真: 0519 86225261
Email: china@forecreu.com - Internet Site: www.forecreu.com.cn

标准导程参数 35°

TSL 35°

螺旋角为 35°的标准导程参数:

	Ø		lead			Ø		lead	
	mm	in	mm	in		mm	in	mm	in
磨 光 材	2.2	0.087	9.9	0.389	黑 皮 材	14.0	0.551	62.8	2.473
	2.7	0.106	12.1	0.477		15.0	0.591	67.3	2.650
	3.2	0.126	14.4	0.565		16.0	0.630	71.8	2.826
	3.7	0.146	16.6	0.654		17.0	0.669	76.3	3.003
	4.2	0.165	18.8	0.742		18.0	0.709	80.8	3.180
	4.7	0.185	21.1	0.830		19.0	0.748	85.2	3.356
	5.2	0.205	23.3	0.919		20.0	0.787	89.7	3.533
	5.7	0.224	25.6	1.007		21.0	0.827	94.2	3.709
	6.3	0.248	28.3	1.113		22.0	0.866	98.7	3.886
	6.8	0.268	30.5	1.201		23.0	0.906	103.2	4.063
	7.3	0.287	32.8	1.289		24.0	0.945	107.7	4.239
	7.8	0.307	35.0	1.378		25.0	0.984	112.2	4.416
	8.3	0.327	37.2	1.466		26.0	1.024	116.7	4.593
	8.8	0.346	39.5	1.554		27.0	1.063	121.1	4.769
	9.3	0.366	41.7	1.643		28.0	1.102	125.6	4.946
	9.8	0.386	44.0	1.731		29.0	1.142	130.1	5.123
10.3	0.406	46.2	1.819	30.0	1.181	134.6	5.299		
10.8	0.425	48.5	1.908	31.0	1.220	139.1	5.476		
11.3	0.445	50.7	1.996	32.0	1.260	143.6	5.652		
11.8	0.465	52.9	2.084	33.0	1.299	148.1	5.829		
12.3	0.484	55.2	2.173	34.0	1.339	152.5	6.006		
12.8	0.504	57.4	2.261	35.0	1.378	157.0	6.182		
13.3	0.524	59.7	2.349	36.0	1.417	161.5	6.359		
				37.0	1.457	166.0	6.536		
				38.0	1.496	170.5	6.712		
				39.0	1.535	175.0	6.889		
				40.0	1.575	179.5	7.066		

STANDARD LEAD 35°

非合同性质文件

版本: 04.2014